

LaserGas™ III SP CO Combustion



All Rights Reserved, Copyright © September 2016, NEO Monitors AS

NEO Monitors LaserGas™ III SP CO analyzer (3rd generation) is specially designed for operation in hazardous areas and it provides real time in-situ CO measurements for virtually any type of combustion control. The configuration is transmitter/receiver units for cross-stack installation. An external junction box simplifies installation and maintenance. The operation principal is based on the well proven Tunable Laser Absorption Spectroscopy (TLAS) implemented using a fast scanning absorption technique with fully digital signal processing. Years of experience allowed us to carefully design this highly compact CO analyzer which offers exceptional performance in harsh environments, is truly robust and provides immediate benefits in terms of operational ease and low cost of ownership.

Features

- In-situ real time measurements
- Fast response time
- Compact design
- Low power consumption (< 10W)
- Suitable for SIL2 applications
- TLAS technology
- Low detection limit
- No interference from other gases
- Not affected by high dust load
- Lifetime calibration, no zero drift
- Integrated span check
- Optional components: CH4, H2O, Temperature
- Ethernet connectivity

Applications

- Combustion control
- Boilers
- To:
- Refineries
- Powerplants
- Chemical industries
- Petrochemical industries
- Steel industries
- and more

Customer benefits

- Reliable in-situ CO measurements in real time
- Process optimization
- Reduce fuel consumption
- Minimize emission
- Simple installation, ease of use
- Low maintenance cost
- No consumables
- No sampling systems
- Compressed air purge (no need for Nitrogen)
- No regular calibrations needed
- Automatic span check available

LaserGas™ III SP CO Combustion

Technical Data

<p>Specifications</p> <p>Detection limit (CO): 0.5 ppm**</p> <p>Max process gas temperature: 1300 °C</p> <p>Max process gas pressure: 1.5 bar abs</p> <p>Optical path length: Typically 0.5 - 20m</p> <p>Repeatability: +/- 0.5 ppm or +/-1% relative, whichever is greater (application dependent)</p> <p>Linearity: < 1% of range</p> <p>Response time: ≤ 5 sec</p> <p>Environmental conditions</p> <p>Operating temperature: -40 °C to +65 °C</p> <p>Storage temperature: -40 °C to +70 °C</p> <p>Protection classification: IP65</p> <p>Inputs / Outputs</p> <p>Analog output (3): 4 - 20 mA current loop (concentration CO, transmission, concentration CH4)</p> <p>Digital output: 10/100 Base T Ethernet (Modbus TCP)</p> <p>Relay output (2): High gas, warning and fault (normally closed)</p> <p>Analog input: 4 - 20 mA process temperature and pressure reading</p>	<p>Ratings</p> <p>Power supply: 24VDC range 18-32 VDC</p> <p>Power consumption: Max. 10 W</p> <p>4 - 20 mA output: 500 Ohm max. load impedance, not isolated</p> <p>Relay output: 1 A at 30 V DC/AC</p> <p>Installation and Operation</p> <p>Flange dimension: DN50/PN10 or ANSI 2"/150 lbs (other dimensions on request)</p> <p>Alignment tolerances: Flanges parallel within 1.5°</p> <p>Purging of windows: Dry and oil-free pressurised air or gas, or by fan</p> <p>Purge flow: 10-50 l/min (application dependent)</p> <p>Calibration: Check recommended every 12 months</p> <p>Safety</p> <p>Laser class: Class 1 M according to IEC 60825-1, eye safe Certified</p> <p>CE:</p> <p>EMC: Conformant with directive 2004/108/EC</p>	<p>Approvals</p> <p>ATEX zone 1: II 2 G Ex d [op is] IIC T4 Gb (TU/RU) II 2 D Ex tb IIIC T78°C Db II 2 D Ex tb IIIC T88°C Db (Lasergas III Ext)</p> <p>CSA: Pending</p> <p>ATEX rating connection box: II 2 GD Ex e IIC T5 Gb -40°C ≤TA≤65°C</p> <p>Functional safety: Designed according to SIL 2; IEC 61508</p> <p>Dimension and weight</p> <p>Transmitter and receiver unit (TU/RU): 215 mm (length, add 50 mm for purge unit) x 125 mm (diameter), 3,5 kg each</p> <p>TU/RU connection box: 260 x 160 x 90 mm, 2,5kg</p> <p>**NOTE: Detection limits are specified as the 95% confidence interval for 1 m optical path and gas temperature / pressure = 25°C / 1 bar abs. Measured in N₂.</p> <p>Special process conditions on request</p>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

*NEO Monitors reserve the right to change specifications without prior notice

Process temperature below 500°C

	Min	Max	LDL/precision
CO	0-50 ppm	0-10000ppm*m	0.5 ppm**
CH4 add-on	0-1% * m	0-10% * m	0.01%
Process path length	0.5	30m	
Process temperature	-40 °C	500 °C	
Process pressure	0.7 BarA	1.5 BarA	

Process temperature above 500°C

	Min	Max	LDL/precision
CO	0-200ppm	0-20000ppm*m	3 ppm
CH4 add-on	0-5% * m	0-10% * m	0.05%
H2O add-on	-	0-40%	2%
Temperature add-on	500 °C	1300 °C	30 °C
Process path length	0.5m	30m	
Process temperature	500 °C	1300 °C	
Process pressure	0.7 BarA	1.5 BarA	

Your local distributor:



NEO Monitors as • A subsidiary of Norsk Elektro Optikk

Prost Stabells vei 22 • N-2019 Skedsmokorset, Norway • Phone +47 67 97 47 00 • www.neomonitors.com